

Crimp Contact Connectors

A quality range of crimp connectors in the standard 9, 15, 25, 37 and 50 position configurations. The connector housings and contacts are offered as separate products, with contacts being available in screw machined and stamped and formed versions, and with a wide choice of plating options. The connector shells are supplied tin plated as standard, and the plug half is indented to maintain performance integrity. Polarisation is achieved by the keystone shape of the mating plug and socket.



Crimp Contacts and Tools (order separately)

Machined crimp contacts

wire sizes 20-28 AWG
Plating options: 0.2, 0.8, 1.3 microns
Gold over Nickel



31D-0084-08



31D-0085-08

Stamped Crimp Contacts

wire sizes 20-28 AWG
Plating options: 0.1, 0.8 micron
Gold over Nickel
Available loose or on reels



31D-0086-08



31D-0087-08



TLG58 - Crimp tool for stamped & formed contacts



TLG52 - Crimp tool for machined contacts



TLG54 - Insertion/Removal

Crimp Tools and Insertion/Extraction Tools

A wide range of tools are available for crimping/inserting/extracting machined and stamped contacts.

Ordering Code

Series:
D = D Subminiature

Product Gender:
P = Plus
S = Socket

Product Version:
C = Crimp snap-in version
(contacts sold separately)

No. of contacts:
9, 15, 25, 37, 50

Termination Style:
This position is not used because contacts are sold separately - insert Z

Contact Plating:
This position is not used because contacts are sold separately - insert Z

Mounting Style:
1 = Standard flanged mounting
12 = 4.40 UNC clinch nuts, rear mounting
(other mounting styles available)

Modification Code:
(011) = Socket with tin plated shell
(012) = Plug with tin plated indented shell

D S C - 25 - Z Z 1 (012)